

(51) International Patent Classification⁶ :

B01D 35/06, G01N 33/553

A1

(11) International Publication Number:

WO 96/26782

(43) International Publication Date:

6 September 1996 (06.09.96)

(21) International Application Number: PCT/US96/00953

(22) International Filing Date: 29 January 1996 (29.01.96)

(30) Priority Data:

08/394,834 27 February 1995 (27.02.95) US

08/487,277 7 June 1995 (07.06.95) US

(71) Applicant: MILTENYI BIOTECH, INC. [US/US]; 251 Auburn Ravine Road, Auburn, CA 94088 (US).

(72) Inventor: MILTENYI, Stephan; Friedrich Ebert Strasse 68, D-51429 Bergisch Gladbach (DE).

(74) Agents: ROWLAND, Bertram, I. et al.; Flehr, Hohbach, Test, Albritton & Herbert, Suite 3400, 4 Embarcadero Center, San Francisco, CA 94111-4187 (US).

(81) Designated States: AL, AM, AT, AU, AZ, BB, BG, BR, BY, CA, CH, CN, CZ, DE, DK, EE, ES, FI, GB, GE, HU, IS, JP, KE, KG, KP, KR, KZ, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, TJ, TM, TR, TT, UA, UG, UZ, VN, ARIPO patent (KE, LS, MW, SD, SZ, UG), Eurasian patent (AZ, BY, KG, KZ, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).


Published

With international search report.

(54) Title: IMPROVED MAGNETIC SEPARATION APPARATUS AND METHOD

(57) Abstract

A magnetic separation column (2) and method for magnetic separation are disclosed herein. The separation column (2) includes a fluid permeable matrix (6) which provides uniform channels that reduce the entrapment of air or non-target substances, and decrease the loss of target substances due to mechanical disruption. Biological target cells are labeled in conjunction with a suitable specific binding member and isolated using the method of the present invention.



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AM	Armenia	GB	United Kingdom	MW	Malawi
AT	Austria	GE	Georgia	MX	Mexico
AU	Australia	GN	Guinea	NE	Niger
BB	Barbados	GR	Greece	NL	Netherlands
BE	Belgium	HU	Hungary	NO	Norway
BF	Burkina Faso	IE	Ireland	NZ	New Zealand
BG	Bulgaria	IT	Italy	PL	Poland
BJ	Benin	JP	Japan	PT	Portugal
BR	Brazil	KE	Kenya	RO	Romania
BY	Belarus	KG	Kyrgyzstan	RU	Russian Federation
CA	Canada	KP	Democratic People's Republic of Korea	SD	Sudan
CF	Central African Republic	KR	Republic of Korea	SE	Sweden
CG	Congo	KZ	Kazakhstan	SG	Singapore
CH	Switzerland	LI	Liechtenstein	SI	Slovenia
CI	Côte d'Ivoire	LK	Sri Lanka	SK	Slovakia
CM	Cameroon	LR	Liberia	SN	Senegal
CN	China	LT	Lithuania	SZ	Swaziland
CS	Czechoslovakia	LU	Luxembourg	TD	Chad
CZ	Czech Republic	LV	Latvia	TG	Togo
DE	Germany	MC	Monaco	TJ	Tajikistan
DK	Denmark	MD	Republic of Moldova	TT	Trinidad and Tobago
EE	Estonia	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	UG	Uganda
FI	Finland	MN	Mongolia	US	United States of America
FR	France	MR	Mauritania	UZ	Uzbekistan
GA	Gabon			VN	Viet Nam

IMPROVED MAGNETIC SEPARATION APPARATUS AND METHOD

Cross Reference to Related Applications

This application is a continuation-in-part of U.S.
5 Patent Application no. 08/394,834, filed February 27, 1995.

INTRODUCTION

Technical Field

The field of this invention is the application of high
10 gradient magnetic separation (HGMS) to the separation of
biological materials.

Background

Magnetic separation is a procedure for selectively
15 retaining magnetic materials in a chamber or column disposed
in a magnetic field. A target substance, including
biological materials, may be magnetically labeled by
attachment to a magnetic particle by means of a specific
binding partner which is conjugated to the particle. A
20 suspension of the labeled target substance is then applied
to the chamber. The target substance is retained in the
chamber in the presence of a magnetic field. The retained
target substance can then be eluted by changing the strength
of, or by eliminating, the magnetic field.

25 A matrix of material of suitable magnetic
susceptibility may be placed in the chamber, such that when
a magnetic field is applied to the chamber a high magnetic
field gradient is locally induced close to the surface of
the matrix. This permits the retention of weakly magnetized

particles, and the approach is referred to as "high gradient magnetic separation" (HGMS).

Previously known or commercially available high gradient magnetic separators generally contain a steel wool or wire matrix. Such matrices often give rise to non-specific binding or entrapment of biological substances or sample components other than the target substance. In addition, such matrices may have non-uniform pores or pathways through which the sample passes, which result in variable separation results. Such non-uniform matrices may also produce magnetic gradients and inconsistent flow patterns that result in the variability of separation results.

The use of HGMS in biological separations requires that the conditions provide a high yield with substantial purity. Accordingly, it would be desirable to provide high gradient magnetic separators, devices and methods that are relatively easy to construct and use, yet provide maximized and uniform magnetic field gradients and flow characteristics during use. It would be most advantageous if such magnetic separators, devices and methods could be used to perform a variety of cell sorting or assay procedures with the selection of the appropriate specific binding member by which the target substance will be magnetically labeled.

25

Relevant Literature

Magnetic separation techniques have been known for many years. The techniques have been used to separate ferrous metal particles from a fluid such as lubricating oil or aqueous slurries of clay, as described in Oder, U.S. Patent No. 3,985,646. In some cases, high gradient magnetic separation was used, for example Windle, U.S. 4,054,513; Dauchez, U.S. 5,137,629; and Friedlaender et al., U.S. 4,526,681. In high gradient magnetic separation, a separation chamber containing a magnetizable matrix made of materials such as steel wool, metal-coated fibers, and metal tacks, bars, plates, fillings, wires or ball bearings, is subjected to a magnetic field. When the magnetic field is

applied, any metal particles in the fluid are attracted to the matrix. To remove the metal particles from the matrix, the magnetic field is turned off or removed, and the chamber is flushed.

5 Developments in biological and diagnostic systems have combined magnetic separation techniques with the use of binding members, such as antibodies, having a specific affinity for a material of interest that is to be separated or isolated from a mixture of materials (Yapel, U.S. 4,169, 10 804; Yen et al., U.S. 4,219,411; Saur et al., U.S. 4,710,472; Owen et al. U.S. 4,795,698; Liberti et al. U.S. 5,200,084). Molday, U.S. 4,452,773 describes the preparation of magnetic iron-dextran microspheres and provides a summary describing the various means of 15 preparation of particles suitable for attachment to biological materials. A description of polymeric coatings for magnetic particles used in HGMS are found in DE 3720844 (Miltenyi) and Miltenyi et al., U.S. 5,385,707. Methods to prepare superparamagnetic particles are described in U.S. 20 Patent No. 4,770,183.

The use of HGMS with biological systems is of interest in the development of diagnostics. In addition, the identification of antibodies specific for many cell surface antigens has lead to an interest in the development of 25 therapeutic methods involving the selection and transplantation of identifiable cells.

A description of a non-magnetic separator may be found in U.S. Patent No. 5,240,856 (Goffe et al.).

30 Summary of the Invention

The invention provides improvements in high gradient magnetic separation devices, apparatus and methods for the separation of biological materials. The subject devices, apparatus and methods allows a greater specificity and 35 efficiency in the isolation of particular cells, proteins, polysaccharides, and other biological materials, or other materials that are magnetic or are capable of a specific

binding interaction with a magnetically labeled binding member.

A magnetic separation column is provided, having a nonmagnetic housing that defines a separation chamber, and
5 a fluid permeable matrix of metallic spheres within the chamber. The spheres form a closely stacked lattice, which creates substantially uniform channels for homogeneous flow during separations. A magnetic separator device may use the separation column in conjunction with a prefilter device.
10 The device may be used in an instrument having a permanent or electromagnet for use during separations, with an optional retractable arm for moving the magnet, pumping means for washing and separating the target material, and a microprocessor for controlling the separation fluid flow.

15

Brief Description of the Drawings

Figure 1 is a schematic diagram of an exemplary separation or prefiltration column of the present invention.

Figure 2 depicts separation and prefiltration columns,
20 together with the sample and collection containers, interconnected by a series of fluid pathways or fluid circuits. The figure also shows the positioning of valves and a peristaltic pump that is used in the preferred embodiment of the separation system.

Figure 3 depicts a computer-controlled unit on which
25 sterile columns, disposable tubing and storage and collection containers, as illustrated in Figure 2, are appended. In a preferred embodiment, the computer-controlled unit contains a magnet, valves and peristaltic
30 pump.

Figure 4 depicts the flow channel formed between three connecting spheres.

Description of the Specific Embodiments

35 Improved magnetic separators, devices and methods for magnetic separation procedures are provided. The improved matrices of the magnetic separators provide uniform pores or channels that reduce the entrapment of air or non-target

substances, decrease the loss of target substances due to mechanical disruption, and have substantially homogeneous flow characteristics. The retention of magnetically labeled material is dependent on the interaction of flow forces and magnetic attraction, therefore a more homogeneous flow improves the separation efficiency.

Biological substances, such as target cells from various systems and organs, are magnetically labeled with a suitable specific binding member, and isolated using the devices and methods of the present invention. The isolation of multipotential cells such as hematopoietic stem or progenitor cells are of particular interest. While hematopoietic cell separation is used herein to provide examples of cell separation procedures, the present invention may be applied to a wide range of cell types or other biological substances.

The magnetic separation system of the present invention can be used to magnetically label and isolate any desired target substance. Of particular interest is the separation of a specific component from a complex mixture. The separation system of the present invention has great versatility, in that almost any target substance may be separated once a specific binding member is available. The target substance or analyte may be any member of a specific binding pair, or a substance associated with a member of a specific binding pair. As an example, a cell surface antigen-antibody binding pair may be used to isolate the antigen itself, cells that express the antigen, a particular organelle involved in processing of the antigen, etc. The devices and methods of the present invention are also advantageously applied to diagnostic techniques involving the binding of a receptor and ligand, such as immunoassays, and the like.

In its simplest form, the cell separation system of the present invention has two main components: a magnetic separator and a cell separation reagent. A schematic diagram of a magnetic separator device is given in Figure 1. The diagram shows the general construction of the separator

and the uniform fluid passage that results from the use of a matrix of metallic spheres. Figure 2 depicts a more complex separation device, including the general positions of fluid passages, collection and storage containers and the separation column. The fluid circuitry can be constructed with integrated valves, or the valves may be applied externally to the fluid pathways.

An optional third component to the preferred cell separation system is a cell separation instrument. Figure 3 depicts a cell separation instrument, preferably computer-controlled, which may incorporate the valves together with a magnet, pump and keyboard control. A device similar to that of Figure 2, constructed without valves, may be mounted directly onto the instrument of Figure 3 for use in the automated separation of target cells.

The cell separation reagent, which may also be referred to as a conjugate, antibody/magnetic particle reagent or magnetic label, includes a magnetically responsive material bound to a specific binding member. There are many well known magnetically responsive materials used in magnetic separation methods. The present invention involves the use of magnetically responsive particles or microparticles. Suitable magnetic particles are described in Molday U.S. 4,452,773 and European Patent Specification 452342-B (published November 20, 1994), which are hereby incorporated by reference. Colloidal sized particles, such as those described in Owen U.S. 4,795,698 and Liberti et al. U.S. 5,200,084, hereby incorporated by reference, are also suitable.

The term "specific binding member" as used herein refers to a member of a specific binding pair, i.e. two molecules, usually two different molecules, where one of the molecules through chemical or physical means specifically binds to the other molecule. The complementary members of a specific binding pair are sometimes referred to as a ligand and receptor. In addition to antigen and antibody specific binding pairs, peptide-MHC antigen and T cell receptor pairs; alternative specific binding pairs of

interest include biotin and avidin or streptavidin; carbohydrates and lectins; complementary nucleotide sequences (including nucleic acid sequences used as probes and capture agents in DNA hybridization assays); peptide
5 ligands and receptor; effector and receptor molecules; hormones and hormone binding protein; enzyme cofactors and enzymes; enzyme inhibitors and enzymes; secretion markers, as described in International application PCT/US93/10126; autologous monoclonal antibodies, and the like. The
10 specific binding pairs may include analogs, derivatives and fragments of the original specific binding member. For example, an antibody directed to a protein antigen may also recognize peptide fragments, chemically synthesized peptidomimetics, labeled protein, derivatized protein, etc.
15 so long as an epitope is present.

Immunological specific binding pairs include antigens and antigen specific antibodies or T cell antigen receptors. Suitable antigens may be haptens, proteins, peptides, carbohydrates, etc. Recombinant DNA methods or peptide
20 synthesis may be used to produce chimeric, truncated, or single chain analogs of either member of the binding pair, where chimeric proteins may provide mixture(s) or fragment(s) thereof, or a mixture of an antibody and other specific binding members. Antibodies and T cell receptors
25 may be monoclonal or polyclonal, and may be produced by transgenic animals, immunized animals, immortalized human or animal B-cells, cells transfected with DNA vectors encoding the antibody or T cell receptor, etc. The details of the preparation of antibodies and their suitability for use as
30 specific binding members are well-known to those skilled in the art.

For brevity, the separation system will mainly be described in terms of its ability to specifically select and separate a defined population of cells (target cells) from
35 a mixed cell population, such as peripheral blood, bone marrow, blood from the umbilical cord or placenta, fetal blood or a leukapheresis product. It will also be appreciated that some tissues may be disrupted into a single

cell or monodisperse suspension to allow isolation of a particular cell subset, such as the separation of tumor infiltrating lymphocytes from a tumor mass, the separation of islet cells from kidney tissue, etc. For example, 5 different cell types may be labeled with a specific antibody to allow cell purging and/or cell enrichment. The target cell population is generally identified by a specific binding member, as described above, which selectively binds to a cell surface antigen present on the target cells. It 10 should be understood, however, that the subject apparatus and method is not limited to such uses.

For simplicity, the specific binding member will be exemplified herein by an antibody. The antibody may be directly or indirectly bound to a magnetic particle. If the 15 antibody is directly bound to the magnetic particle, then the target cell population is magnetically labeled when the antibody binds to the cell surface antigen. If the antibody is indirectly bound to the magnetic particle, then the target cell population is susceptible to magnetic labeling 20 when the antibody is bound to the target cells. The antibody-bound cell population is actually labeled by further contacting the cells with a specific binding member for the antibody, where that specific binding member is itself bound to a magnetic particle. The target cells, 25 identified by such magnetic labeling, are then separated from other cells by means of a magnetic field. For example, a specific binding member such as avidin can be conjugated to a magnetic particle where the avidin binds to a biotinylated antibody that in turn specifically binds to the 30 target cells.

The specific binding member may be directly attached to the magnetic particle. This may be accomplished by means of reactive groups on the specific binding member and magnetic particle themselves. Alternatively, the specific binding 35 member and magnetic particle may be joined by means of a coupling agent or linker. The terms "coupling agent" or "linker", as used herein, include various bifunctional crosslinking or coupling agents, i.e. molecules containing

two reactive groups or "ends", which may be separated by a spacer.

Conventional high gradient magnetic separation matrices are typically prepared from materials such as wires, metal-coated fiber or steel wool. In the improved magnetic separation device of the present invention, the gradient-intensifying matrix of the high gradient magnetic separator is formed from small spheres of magnetically susceptible or ferromagnetic material. Such materials include, but are not limited to iron, steel, cobalt nickel, and other ferromagnetic rare earth metals or alloys thereof. For example, the matrix material may include ferromagnetic metal spheres such as iron spheres (e.g. MARABU Balls, Kugelfabrik Schulte & Co., Wermelskirchen, Germany). Many different methods of manufacturing spheres are known. Usually the spheres have an average diameter ranging from about 0.2 to 1.5 mm for the separation of large cells or cell complexes, and about 0.05 to 0.2 mm diameter for subcellular material. Preferably, the spheres have an average diameter ranging from about 0.2 to 0.5 mm, and most preferably, the spheres are selected to have an average diameter ranging from about 0.2 to 0.3 mm. It is desirable that the size of spheres be relatively homogeneous, usually varying not more than about 15% from the average size, more usually by not more than about 10%, and preferably by not more than about 5%.

The substantially symmetrical spherical shape and substantially uniform size of the spheres are desirable for the construction of a magnetic separator matrix, as the spheres can assume a lattice configuration wherein the gaps between the spheres form regular channels or pores in the matrix. The lattice configuration is a patterned framework of spheres that forms channels of regular size between adjacent spheres and throughout the matrix. Upon the application of a magnetic field to the separator, magnetic field gradients are created in the gaps between the spheres. The uniform size, and therefore spacing, of the spheres provides for a substantially uniform magnetic gradient throughout the matrix, and substantially uniform fluid flow

characteristics. A flow channel is depicted in Figure 4. The dimensions of the channel can be described by the maximum size ball or particle that would fit between the matrix spheres. With reference to Figure 4, the geometrical relationship is $r = \sim 0.155 R$. It will be appreciated from the teachings of the present invention that the channel size may be adjusted to an average diameter optimal for the desired separation process by varying the size of the spheres that are used to form the matrix.

The spherical shape provides for the formation of a substantially stable matrix structure when the spheres are packed within a housing that defines a separation chamber. As described in detail below, the matrix is also coated with a substantially fluid impermeable material such as a plastic polymer. On application of a plastic polymer coating, the tight gaps between the spheres are closed, resulting in a hydrodynamically optimized matrix. The resulting ferromagnetic matrix will usually occupy about 60 to 75% of the total volume of the separation chamber, and will be permeable to fluids. The impermeable coating will occupy about 1 to 5% of the total volume. The free volume will range from about 20 to 40% of the total separation chamber volume. In a preferred embodiment, the total matrix will occupy about 75-80% of the total volume of the separation chamber.

Figure 1 presents a schematic of an exemplary separation column. The spheres are not depicted at scale, but so as to better depict the formation of a three dimensional fluid permeable matrix 6. The spheres are packed in a housing 4 which is made of a non-magnetic material. The magnetic separator housing serves as the body of the separation column, and the interior of the housing defines a separation chamber. Housings of various lengths, shapes and diameters are advantageously made of plastic. Suitable nonmagnetic materials for the construction of a magnetic separator housing include stainless steel, glass, plastic, etc.

In one preferred embodiment, the magnetic separator housing is a plastic that the matrix coating will adhere to, allowing improved hydrodynamic properties at the boundary of the matrix and housing. It will be appreciated that the coating material and housing material will be selected for compatibility with one another, e.g. a lacquer coating must be selected that will not result in non-adherent plastic debris accumulating in the column. Various mechanisms are known by which materials adhere to each other, and may be exploited for this purpose. Conveniently, the selection for compatibility may be made based on the solvent used in conjunction with the lacquer. The solvent will be slightly reactive with the plastic housing, such that the lacquer in the solvent will adhere, but not so reactive that the structural integrity of the column is compromised during the lacquer curing process. For example, the coating material may be selected to include a solvent that causes a slight dissolution of the interior of the plastic housing. Upon curing, the plastic rehardens thereby bonding or sealing the coating material and housing material to each other. One of skill in the art will appreciate that information regarding such reactivity is generally available. Exemplary of a suitable solvent and housing combination is methylethylketone and the plastic ULTEM® (General Electric).

Preferably, each of the materials selected for the construction of separation column 2 will also be compatible with sterilization procedures. Preferably, the housing is cylindrical in shape to facilitate the flow of sample through the separation chamber as well as the formation of three dimensional matrix 6 within the housing. The walls of the housing preferably have a thickness of about 1 to 3 mm. The separation column has inlet 12 and outlet 14 ports for the introduction and discharge of fluids. Generally, the inlet and outlet ports are narrow structures relative to the main body of the housing. This facilitates the attachment of the separator to further fluid circuitry in a separation system and advantageously maintains the device as a closed system. The inlet and outlet ports may be positioned at

different sites than as depicted in Figure 1, but it will be appreciated that the overall structure of the separator will preferably provide a separation chamber having the fewest bends or corners which might otherwise slow fluid flow or
5 create spaces where sample might accumulate.

At the inlet and outlet of the column, the column is constructed to have a feeding mechanism ensuring optimal homogeneous distribution and flow through the matrix. The distribution mechanism is comprised of the volume in front
10 of cap layer 8 and the cap layer itself, which serves as a flow resistor. The distribution volume (in milliliters) may be defined relative to the width of the column (in millimeters), usually having a ratio of about 0.1 to 10. The chamber volume in front of base layer 10, as well as the
15 base layer itself, also serves as feeding mechanism for fluids passing into the chamber via the outlet port.

It is preferable to have column dimensions where the diameter to length ratio is at least 0.2 to 1. The actual dimensions of the column will depend on the material being
20 separated, and the desired flow rate for separation. The column dimensions will provide a chamber that will accept a matrix having an adequate surface area to create sufficient magnetic field gradients in the separation chamber and permitting efficient retention of magnetically labeled
25 material. The volume necessary for a given separation may be empirically determined, and will vary with the size, antigen density on the cell surface, antibody affinity, etc. As an example, a sectional area of 3 cm² allows a flow rate of 5 to 40 ml/minute. The binding capacity of a 2 x 4 cm
30 matrix is approximately 10⁹ labeled cells.

To facilitate the manufacture of the separation column, base layer 10 of nonmagnetic porous material is positioned in the housing such that when the ferromagnetic spheres are placed in the chamber they do not pass through outlet port
35 14. Suitable porous materials for the formation of the base layer include, but are not limited to, porous plastic, sintered metals or glass, grids, etc. For example, various porous frits available from Porex Singwitz, Germany, may be

used. Usually, the porous material will have a pore size of about 20 to 200 μm , preferably 50 to 150 μm . A suitable pore size will be selected according to the dimensions of the target substance and the make up of the sample material.

5 In addition, the pore size will not be so large as to allow the spheres to fill the porous openings of the layer material. Following the insertion of the spheres into the chamber, the housing may be shaken or vibrated to facilitate the settling of the spheres into a more uniform

10 configuration. Optionally, cap layer 8 of nonmagnetic porous material is positioned in the housing over the matrix to maintain the uniform configuration of the matrix during storage, handling and use. Pressure may also be applied to cap layer 8 to more firmly pack the spheres within the

15 chamber. Upper portion 16 of the separation column, which includes inlet port 12 in this embodiment, is then positioned on the top of housing 4 and is attached to the housing. For example, when using plastic materials, upper portion 16 might be glued or ultrasonically welded to

20 housing 4 to complete the formation of the separation column. Following the completion of the housing, the matrix is coated.

With reference to Figure 1, a coating is applied to the fluid permeable matrix described above. The coating is

25 selected to be substantially impermeable to ions, and therefore protects the metallic matrix material from corrosion as well as inhibiting the escape of cations from the matrix, which might damage the cells. In addition to the formation of an impermeable protective layer over the

30 matrix material, a complete coating of the matrix closes the gaps between spheres, providing both mechanical stability to the matrix, and a hydrodynamically optimized matrix. Such mechanical stability is particularly advantageous when the matrix is formed from small spheres of magnetically

35 susceptible or responsive metal, as described above. A coating material, such as a lacquer coating, may be flowed into inlet port 12 of the separation column. The lacquer flows through cap layer 8, matrix 6 and base layer 10,

thereby coating the porous surfaces of each component. Excess lacquer is allowed to pass from the chamber through outlet port 14. The coated separation column may be centrifuged to further expel excess coating material from the chamber. The coating is then allowed to dry. The separation column may be heated to further promote the drying of the coating. For example, the coated separation column may be placed in an oven at 110°C for four to five hours, followed by continued drying at room temperature for three to seven days.

Upon drying, the coating hardens, thereby providing mechanical support to the matrix. Not only does this mechanical support aid in maintaining the integrity of the matrix during the storage and handling of the separation column, it also provides the matrix with a rigid structure which does not exhibit significant elasticity. This rigidity is advantageous because the matrix might otherwise be deformed upon the application of an external magnetic field to the separation column. The applied magnetic field strength of the external magnetic means is typically within a range of about 0.1 to about 1.5 Tesla, and more preferably between about 0.2 to about 0.8 Tesla. The field strength should be great enough and the distance between the magnet and the separation column should be small enough to induce intensified magnetic field gradients within the matrix. To maintain uniform magnetic gradients in the separator, the matrix material should not move or shift in the chamber upon the application of the magnetic field. The spherical metallic components, the housing and the coating are advantageously combined in the present invention to provide an improved matrix with sufficient rigidity to resist substantial deformation when the separation column is placed within a magnetic field.

It is preferable to coat the matrix while the spherical metallic components are within the separation column housing. Coating the matrix within the housing avoids disrupting the matrix after the coating has been applied. Moreover, coating the matrix within the housing serves to

fill or seal small void spaces, interstices or crevices formed near the contact points between the spheres, as well as between the spheres and housing, while simultaneously providing a uniform surface to the channels or pores formed
5 by the separated points of the spheres. These channels or pores result in the permeability of the matrix. By sealing the void spaces, there is a decrease in the areas where cells or other solid components of the sample might wedge or become physically entrapped, even in the absence of a
10 magnetic field.

In the completed separation column, the selection of matrix and coating materials will preferably result in channels or pathways through the permeable matrix having an average diameter ranging from 20 to 60 μm and an occupying
15 volume of about 60% to 80% of the total volume of the separation chamber. For example, a separation column for the separation of blood cells may have a final coated-channel size averaging 20 μm , with the matrix occupying approximately 80% of the total volume of the chamber.

20 Following the preparation of the substantially impermeable coating, the matrix and other interior surfaces of the separation chamber are preferably further treated by the addition of a hydrophilic material such as polyvidone (BASF, Ludwigshafen, Germany). Other suitable hydrophilic
25 coating materials include, but are not limited to, polyvinylpyrrolidone, polyethylene glycol, hydroxyethyl starch, and other hydrophilic coatings, such as acrylamides, surfactants or detergent-type wetting agents, and biological material including, but not limited to, heparin and human
30 serum albumin. The interior surface of the separation chamber may also be made hydrophilic by plasma or corona etching of the surface. The hydrophilic coating provides the interior of the separation column and the fluid permeable matrix with a readily wettable surface. By
35 enhancing the wettability of these surfaces, the introduction of fluid into the separation column will produce a uniform fluid front as it passes through the chamber. This in turn facilitates the removal of air

bubbles from the permeable matrix and other void spaces in the separation chamber. It is desirable to maintain the separation column and other device components as a closed system substantially free of air during the separation process. The presence of air in the system during the separation of target cells affects the interior surface tensions and unventilated areas, which can lead to cell destruction.

Referring to Figure 2, which depicts an improved separation device, separation column 40 may be preceded by a prefiltration device. The figure depicts the prefiltration device as a column 30, however it will be understood that other configurations, such as prefilter, may find use. The prefiltration column is generally a three dimensional structure that may be substantially identical to the separation column in terms of its structural composition. The prefiltration column, however, may have different dimensions, the matrix may be made of spheres having a different composition, e.g. a non-ferromagnetic material, or the matrix may be made of spheres having a different diameter from those used in the separation column, thereby providing a pore or channel size different from that found in the separation column. In one embodiment, the prefiltration column is identical to the separation column. Passage of the sample through the prefiltration column serves to trap and remove fluid components that are not desired in the final separation product. For example, in blood cell separations, "sticky" cells such as monocytes, granulocytes and platelets may be removed from the cell suspension by the prefiltration column. Alternatively, the prefiltration column may be constructed to have an average pore size that is smaller than that found in the separation column. For example, the pore size of the permeable matrix may be selected to remove large tumor cells from the sample prior to the fluid's passage through the separation column. The passage of the fluid sample through the prefiltration column may also serve to break apart aggregates, such as cell aggregates, that may exist in the fluid. Moreover,

because the prefiltration column contains materials substantially identical to those of the separation column, those sample components that might nonspecifically bind to the separation column are advantageously caught by the
5 prefiltration column. Thus, the prefiltration column reduces the possibility of fouling the separation column during the separation process, and it reduces the collection of unwanted cells or fluid components in the final separation product.

10 Referring to Figure 2, a preferred embodiment of separation device 25 is depicted. Sample container 81 is connected to an optional suspension filter 35. The suspension filter may be used to remove unwanted particulate components from the fluid sample and is selected to have a
15 pore size sufficient to remove particulates above a certain size. For example, the suspension filter may be a Pall Filter (Pall SQ40S; Pall Biomedical, Inc., Puerto Rico) having a pore size selected to remove particulates larger than 40 μm , such as cell clots and clumps in hematopoietic
20 cell samples. The suspension filter is connected by fluid pathway two 12 to inlet port 32 of prefiltration column 30.

Outlet port 34 of the prefiltration column 30 is connected by fluid pathway five 15 to inlet port 42 of separation column 40 to which the magnetic field will be
25 applied in the course of the separation process. Outlet port 44 of the separation column is connected by fluid pathway eight 18 to distribution channel 88 which leads to product collection container 83, final wash waste container 84 and unlabeled sample container 85. Separate fluid
30 pathways nine 19, ten 20, and eleven 21 lead to these containers, respectively.

This separation device further includes a wash or buffer container 80 and an initial wash waste container 82, which are connected by fluid pathways one 16 and three 17,
35 respectively, to fluid pathway two 12. Buffer container 80 is also connected via wash or buffer line 90 (fluid pathway six) to distribution channel 88. The buffer line is further connected to fluid pathway five 15 by means of fluid pathway

four 14. The fluid pathways, containers, filters and columns may be coupled to one another by means of any suitable means such as standard spikes, Luer locks, male-female connectors, T-connectors, Y-connectors and 4-way
5 connectors or other fittings as are commonly used in intravenous solution delivery sets.

Fluid flow through the fluid circuitry of the separation device can be controlled by means of valves placed within the fluid pathway(s). Fluid pathways one
10 through eleven are associated with corresponding valves one through eleven (1-11). The valves may be inside the pathways themselves or may be external to the pathways. The fluid flow may also be controlled by a pump. For example, when the fluid pathways are made of a flexible material,
15 such as flexible tubing, suitable valves for the control of fluid transport include pinch valves. The pinch valves close the fluid pathway by depressing the walls of the tubing against one another. It will be appreciated by those skilled in the art that such pinch valves will be selected
20 to accommodate the size of the tubing chosen for use as a fluid pathway. In addition, the compression force of the pinch valve will be selected to achieve the compression of the chosen tubing and thereby effect the closure of the fluid pathway. The valve specifications, therefore, will be
25 matched to the softness or hardness (durometer) specifications of the selected tubing.

The most preferred embodiment of the separation device further includes recirculation loop 92 (fluid pathway seven) such that fluid that has already passed through separation
30 column 40 may be recirculated through the separation column. Typically, a pump 64 will be connected to the recirculation loop to facilitate the recycling of fluid through the separation column as well as control the flow through the column. It will be appreciated by those skilled in the art
35 that a variety of pumps may be used. An exemplary pump is a peristaltic pump that can control the passage of fluid through the recirculation loop in either direction and at variable speeds. The separation device having a

recirculation loop allows sequential separations on one column, by a process of binding and elution, followed by a second binding and elution. Sequential separations provide improved purity in the final target population.

5 Figure 2 schematically depicts a preferred embodiment of a separation device. It will be appreciated, however, that a separation process may be accomplished using the basic system components, i.e. the improved magnetic separator and collection containers.

10 It will be appreciated by those skilled in the art that the recirculation means and fluid flow pathways of the present invention are also suitable for use in alternate separation systems. For example, the recirculation means may be advantageously used in a system wherein the
15 separation means involves centrifugal techniques, absorption columns or chemical means as alternatives to the magnetic or electromagnetic separation means.

 In an exemplary cell separation process, the fluid pathways and columns are primed by allowing a wash liquid to
20 flow through all of the fluid pathways and columns, preferably at varying flow speeds and pressures. The wash liquid may contain materials such as a physiologically acceptable protein, such as human serum albumin (HSA), which inhibits cells from adhering to the interior surfaces of
25 plastic device components. The wash liquid may also contain small quantities of physiologically acceptable surfactants or detergents, to improve the wetting of the interior surfaces.

 It is found that large air bubbles in the fluid
30 pathways are detrimental to the recovery of viable cells. Methods of removing air bubbles from fluid pathways are known in the art, and may be employed for this purpose. A method of particular interest exploits the observation that a permeable frit such as those used in the cap layer and/or
35 base layer will not allow passage of air bubbles at fluid flow rates of less than about 400 ml/minute. A column may be cleared of air bubbles by circulating wash liquid through a recirculation loop at flow speeds of less than about 400

ml/minute. The air bubbles then accumulate outside of the column at the base and/or cap layers. The direction of flow is then reversed, and the bubbles are washed out of the system into a suitable waste bag. Preferably, the sequence
5 is repeated to ensure the removal of all bubbles. The existing bubbles may be intentionally enlarged by the generation of negative pressure.

In such an exemplary process, magnetically-conjugated antibodies may be used to specifically target the desired
10 cells in a mixed cell population. The magnetic reagent is incubated with the mixed cell population, then unbound particles are washed away by any convenient means, e.g. centrifugation, etc. When cell sterility is desired, the antibody incubations and washes may be performed in a closed
15 container process, where the antibodies and wash liquids are added to a sterile container by means of a sterile syringe or similar device. In this way, contamination of the desired cells by air-borne microorganisms is minimized. In such a closed system, particularly where the container is a
20 flexible bag, the mixing of cells and antibody may be improved by injecting a small amount of sterile air, at a ratio of from about 0.5 to 2 of air to liquid, into the container.

The incubated cell suspension, now containing
25 magnetically labeled target cells, is passed through the separation device. The system transports the cells through a magnetic separator which is positioned within or is adjacent to a magnetic field. The source of the magnetic field may be a permanent magnet or an electromagnet. The
30 separation column is preferably constructed to include a ferromagnetic matrix of stacked ferromagnetic spheres, as described above. Optionally, the sample is passed through a prefiltration column, also constructed as described above, prior to passage through the separation column. If the
35 separation column contains a matrix comprised of other than ferromagnetic spheres, then the sample may be first passed through a prefiltration column that is substantially identical to that separation column.

The magnetically labeled cells accumulate in the separation column in response to the magnetic field. The non-labeled cells and other suspension components pass through the separation column and into an unlabeled sample container and/or waste container. The labeled or purified cells may then be eluted from the separation column by either removing the separation column from the magnetic field or removing the magnetic field from the separation column. A wash solution, such as a buffered liquid, is passed through the separation column to wash the labeled cells from the separation column and into a product collection container. The collection container may be used for further processing of the target cells or cryopreservation of the target cells.

In preferred embodiments, the separation column is a high gradient magnetic separation column constructed from ferromagnetic spheres, as described above. The containers referred to herein are typically plastic bags, such as those used for the storage and delivery of intravenous fluids, but any suitable containers can be used. The containers will be selected for their necessary storage or collection volume, their capacity for sterilization and their ability to be used in a closed system, i.e. a separation system from which substantially all of the air can be removed prior to use.

In another preferred embodiment, the magnetically labeled cells are recirculated through the separation column to enhance the selection of the target cells and the removal of unwanted cells or other suspension components. Some preferred embodiments also include the use of a prefiltration column. The prefiltration column, however, is not subjected to a magnetic field. Instead, the preliminary passage of the cell suspension through the prefiltration column results in the capture of suspension components or materials that otherwise might nonspecifically bind to the separation column. Such nonspecific binding may cause the blockage or fouling of the separation column, which could in turn inhibit or reduce the separation and collection of the labeled cell population.

The fluid pathways, collection containers, suspension filter, prefiltration column and separation column, may be constructed, interconnected and supplied as a disposable separation device. The target cells are preferably
5 collected in a sterile blood transfer container from which the cells can be transplanted to the patient or in which the cells can be stored or subjected to further processing. The complete cell separation device may be prepackaged in suitable containers. The prepackaged device can be
10 sterilized and provided ready for use in the improved magnetic separation process of the present invention. The reagents necessary for the desired separation process may also be provided in kit form. For example, a conjugate specific for the target cell population or other analyte may
15 be provided separately from, or with the device. The kit may also include wash solutions, for example standard sterile saline solution, and/or other buffered liquids, such as phosphate buffered saline, 1 mM EDTA and 0.5% human serum albumin. These reagents or other solutions can be provided
20 in containers such as plastic bags that can be connected to the appropriate fluid passages of the cell separation device.

The improved separation system of the present invention may be totally automated. In the automated system, a
25 computer controls the flow of fluids through the fluid circuitry and separation column, controls the magnetic field strength or placement of the magnet and/or separation column to provide for the retention and release of the magnetically labeled target cells or analyte, and directs the final
30 collection products into appropriate containers.

One embodiment of an automated cell separation instrument, as depicted in Figure 3, includes mechanical, electromechanical and magnetic components. The mechanical components may include: an instrument outer shell or housing
35 15; adjustable container holder 21; peristaltic pump 64; prefiltration column holder 32, and separation column holder 42. The electromechanical components may include: solenoid pinch valves 1-11; an internal motor (not shown) to drive

peristaltic pump 64; an internal motor (not shown) to move separation column holder 42 (and thereby move the separation column 40) into or out of the magnetic field, or to move the magnet 50; and a bubble detector (ultrasonic sensor) 65, which is used to detect the presence of fluid in the fluid circuitry. The magnetic means may include permanent and electromagnets. It will be appreciated that these individual components may be selected from a number of readily available alternates and may be combined in a variety of configurations without departing from the general description of the improved magnetic separation system of the present invention.

In a preferred embodiment of the separation device, the fluid pathways, solution and collection containers, suspension filter, prefiltration column, separation column and connectors are provided as a preassembled disposable component to the separation system. The separation device is mounted on the separation instrument for the performance of the separation process. Upon completion of the separation process the product collection container may be removed, and the remaining separation device components are disposed.

Preferably, an onboard microprocessor (not shown) controls all of the electromechanical components of the instrument, and software directs the system to perform the appropriate operations in a standard sequence. A video display 62 and operator keypad 60 allow the operator to monitor automatic system operation and to control instrument operation in a manual mode. A printer (not shown) may be connected to the microprocessor for printing process information, labels, etc.

Figure 3 depicts a separation instrument and mounted separation device. In this embodiment, the separation device is mounted or installed upon the instrument by positioning the tubing of the fluid pathways in their respective external pinch valves 1-11, as described above. Prefiltration column 30 is placed within prefiltration column holder 32. Separation column 40 is placed within

separation column holder 42 which is moved relative to magnet 50 by means of retractable arm 44. Adjustable clamp 20 is used to secure hanger arm 21 in a raised position. There are mounts or pegs 22 on the hanger arm on which to place initial wash waste container 82 and buffer and sample containers (not shown) as appropriate. The apparatus may further include storage compartment 70 to separate the final waste container and unlabeled sample container from the product collection container (not shown).

10 The following examples are offered by way of illustration and not by way of limitation.

Examples

Example 1

15 Separation Column/Prefiltration Column

With reference to Figure 1, a cylindrical housing 4 of nonmagnetic material is selected having a diameter of 20 mm and a total volume of about 14 ml. A first porous frit (polypropylene) is placed in the base of the housing thereby forming base layer 10. The base layer has an average pore size of approximately 100 μm . Ferromagnetic iron spheres are added to the chamber. The spheres have an average diameter of about 0.2 to 0.5 mm, and approximately 60 grams (55 to 65 grams) of the spheres are placed in the container.

20 To avoid overfilling of the chamber, a 0.12 gram tolerance is preferable. The use of spheres having substantially uniform diameters allows the spheres to assume a symmetrical configuration as depicted in Figure 1 wherein the spheres are stacked in closely interconnected layers.. The housing is then vibrated for approximately five seconds to settle the spheres into a uniform matrix 6. A second porous frit or cap layer 8 is placed over the settled spheres and may be pressed into the chamber to further compress and/or hold the spheres in a stacked matrix configuration or lattice-like structure. Upper portion 16 of the separation column is then attached to the top of the housing. The area around inlet port 12 and outlet port 14 may be shaped to facilitate the secure connection of the column to a fluid pathway such

35

as plastic tubing. Such a column, may further include stops
18 which will inhibit the tubing from passing beyond a
certain point on the column. The ports may also be formed
to include any suitable connecting means such as spikes,
5 luer locks, male-female connectors, etc.

The matrix may be coated as described above. Once the
coated matrix has been allowed to dry, the separation column
is further treated with about 5 ml of 1% polyvidone, or
other suitable hydrophilic material. Excess polyvidone is
10 allowed to pass through outlet port 12, and the separation
column is dried.

Example 2

Cell Separation Process

15 The following cell separation process is exemplified by
the separation device of Figure 2.

Background

In determinations for optimal flow rates, it was found
20 that most of the desired result of a sequence, e.g. washing,
eluting, etc. occurs in a short period of time, with longer
flow cycles providing little additional benefits. In order
to maximize performance, several short cycles are executed
in place of one long cycle. This provides improved
25 performance with no net gain in time or volume pumped. In
this way, the loss of cells, the physical impact on cells
during elution, and the residual contamination are all
minimized.

30 Priming of the separation device

The first phase of the cell separation process involves
the filling or priming of the fluid pathways, the suspension
filter, and the prefiltration and separation columns.
During the priming process, the magnetic field is typically
35 not applied to the separation column. The priming of the
device serves to remove air from the separation system as
well as wash the hydrophilic coating (e.g. PVP) from the

prefiltration and separation columns. Flow is induced by gravity in some steps and with a pump in others.

The fluid pathways and column are cleared of air bubbles by circulating wash liquid through a recirculation loop at flow speeds of less than about 400 ml/minute. Several cycles at different flowrates are used. The different flowrates induce different flow characteristics through the separation device, as well as negative pressures, both of which aid in dislodging bubbles from the tubing and column. The air bubbles then accumulate outside of the column at the base and/or cap layers. The direction of flow is then reversed, and the bubbles are washed out of the system into a suitable waste bag. The sequence is repeated for 6 cycles of approximately 5 seconds each to ensure the removal of all bubbles. A cycle of about 4 seconds provides for the collection of about 90% of the bubbles. Each successive cycle removes approximately 90% of the previous balance.

Valves 6 and 10 are opened to allow a buffer or other wash solution to flow from the buffer container 80 and pass through the buffer line 90 to the final waste container 84. Valve 10 is closed, and valves 8, 5 and 3 are opened to prime separation column 40 and prefiltration column 30, thereby removing air bubbles and washing the hydrophilic coating from the columns. The waste and bubbles are transported to the initial wash waste container 82. The pump 64 may be activated to facilitate the transport of the wash liquid through the designated pathway rather than using gravity to induce flow through the system. Valve 10 is reopened to allow further gravity drainage of bubbles to the final waste container 84, and the valves are closed. The wash liquid may contain materials such as human serum albumin, which inhibits cells from adhering to the interior surfaces of plastic device components.

Valves 4, 7, 8 and 10 are then opened to prime recirculation loop 92. The pump is activated to circulate buffer through separation column 40 in both clockwise and counterclockwise directions via the recirculation loop.

This recirculation process is repeated for the passage of the buffer through both ends of the separation column to sequentially collect and remove remaining air bubbles from the porous matrix and other void spaces of the separation column and to thoroughly wet the interior of the separation column. The recirculation process also serves to further rinse any hydrophilic coating from the separation column. The valves are then closed.

Valves 1, 2 and 3 are opened to allow priming of the suspension filter 35. The valves are then closed. Valves 6, 8, 5 and 2 are then opened to allow passage of the buffer up to the sample container 81. All valves are then closed. In an automated system, ultrasonic sensor 65 is situated next to fluid pathway two 12. If any air bubbles enter the system from the sample container, the interrupted fluid flow in the pathway is detected, and the instrument automatically switches to wash mode. All valves are closed until the operator can remove the air bubble.

20 First Collection of Magnetically Labeled Cells

In the collection phase, a magnet is positioned relative to separation column 40 such that a magnetic field is applied to the separation column. Relative positioning may entail moving a magnet around or adjacent to the separation column, or moving the separation column into the magnetic field. In one embodiment of the present invention where a permanent magnet is used to provide the magnetic field, it is advantageous to maintain the magnet in a fixed position as it is a relatively heavy component of the separation system. Thus, the separation column is mounted in or attached to an arm means (not shown) which serves to retract the separation column into the magnetic field for the separation phase and then displace the separation column from the magnetic field for the elution and/or wash phases.

In this example, the separation column 40 is retracted into the magnetic field of a permanent magnet. Valves 1, 5, 8 and 11 are opened to draw air bubbles from the bottom of prefiltration column 30 and separation column 40, and the

valves are then closed. Valves 6, 8 and 4 are opened to draw any air bubbles to buffer line 90. Valves 8 and 4 are closed, and valve 10 is opened to allow the gravity drain of the buffer to final waste container 84. All valves are then
5 closed.

Valves 2, 5, 8 and 11 are opened to initiate the flow of sample from sample container 81 and its sequential transport through suspension filter 35, prefiltration column 30 and separation column 40. The target cells or analyte
10 which have been bound by a magnetic reagent are retained in the separation column in the presence of the magnetic field. Unlabeled cells and/or other fluid components pass through the system and are collected in unlabeled sample container 85. This process continues until the sample container
15 empties and an air bubble is detected in fluid pathway two 12. The valves are then closed.

First Wash of the Separation Column

A first wash of the fluid circuit is accomplished by
20 opening valves 1, 5, 8 and 11 to allow the passage of buffer through the prefiltration and separation columns. The pathway is washed and empties into unlabeled sample container 85. Valves 1 and 5 are closed, and valves 7 and 4 are opened to allow a gravity wash of recirculation loop
25 92. The valves are then closed. The unlabeled cell container is advantageously connected to the fluid circuit on a separate fluid pathway so that the unlabeled cells are not destroyed or contaminated during the separation process.

Valves 4, 8 and 10 are opened to allow the buffer to
30 rinse the separation column to final waste container 84. The valves are then closed.

Valves 6, 5, 8 and 3 are opened to transport fresh buffer back through the system, including the prefiltration column 30. This is a safety procedure to remove residual
35 cells on top of the connectors. The valves are then closed. Valves 4, 8 and 10 are reopened to allow the buffer to rinse the separation column 40 to final waste container 84. The valves are then closed.

Valve 7 is opened, and pump 64 is activated to backwash the separation column 40 with buffer entering the separation column by means of outlet port 44. Valves 4, 8 and 10 are then opened to allow the gravity rinse of recirculation loop 5 92 into final waste container 84. Valve 7 is closed, and buffer washes the separation column to the final waste container. All valves are then closed. This sequence is repeated 3 times using short cycles, to improve the effectiveness and allow the use of lower flowrates.

10 A pump means is advantageously used in this and other steps in the separation process. Not only can a pump change the direction of fluid flow, or fluid circulation in conjunction with the recirculation loop, but it may also be operated at different speeds. The different speeds allow 15 the fluid to be pumped at variable rates and to be transported through the system without depending upon gravity alone. For example, a wash of the separation column or fluid pathways may be performed at an increased speed to better clear nonspecifically bound materials from the 20 system. In addition, the pump in conjunction with the recirculation loop allows for the agitation of fluid through the system. Such agitation can be also be used to help wash wanted or unwanted sample materials through the system.

25 First Elution of Separated Cells from the Separation Column

Valves 6 and 11 are opened to rinse distribution channel 88. The valves are all closed, and the magnet is turned off or the separation column 40 is removed therefrom. Valve 7 is opened, and buffer is transported through 30 separation column thereby washing the separated magnetically-labeled cells from the separation column. Pump 64 may be used to facilitate the transport of the buffer back and forth through the separation column to repeatedly backwash and wash the labeled cells from the separation 35 column. Valve 7 is then closed.

It is possible that some labeled or unlabeled cells may become physically trapped or wedged inside the porous matrix or other void spaces of the separation column as the sample

is passed down through that chamber. By backwashing the separation column, (i.e., transporting the wash solution up through separation column outlet port 44, through the matrix and out inlet port 42) the recovery of separated cells is enhanced by pushing any entrapped cells back through the chamber in the direction from which they entered. This is clearly preferable to forcing the cells through the matrix in the elution phase and thereby possibly rupturing the cells.

10

Re-collection of Magnetically Labeled Cells

In a preferred magnetic separation process, a second collection or re-collection of the magnetically labeled cells is performed. The magnet is turned on or the separation column 40 is again placed within the magnetic field. Valve 7 is opened, and the fluid containing the labeled cells is recirculated through the separation column via recirculation loop 92. Preferably, the fluid is circulated counterclockwise. This results in the entry of the labeled cells into the separation column via separation column outlet port 44. This in turn results in the re-collection of the majority of the magnetically labeled cells in the lower portion of the separation chamber from which the cells may be readily eluted. Valves 6, 8, 5 and 3 may be opened to clear the lower fittings or connectors of any labeled cells for re-collection in the separation column. The valves are then closed. Valve 7 may also be reopened to clear the recirculation loop of any labeled cells for re-collection in the separation column.

30

Second Wash of the Separation Column

A second wash of separation column 40 may be performed. The fluid is circulated through recirculation loop 92 to wash the lower portion of the separation column. Valves 4, 8 and 10 are opened to allow for the gravity rinse of the recirculation loop and passage of the rinse buffer to final waste container 84. The valves are then closed. This sequence of steps may be repeated. Valves 6 and 11 are

opened to clear distribution channel 88, and then the valves are closed. This sequence is repeated 3 times using short cycles.

5 Final Elution of Labeled Cells from the Separation Column

The magnet is again turned off or removed. Valves 4, 8 and 9 are opened, thereby allowing buffer to wash the magnetically labeled cells from the bottom of separation column 40 into product collection container 83. Valve 7 may
10 be opened and pump 64 may be activated to backwash cells from the separation column. The pump is then stopped to allow the continued wash of the separation column to the product collection container. This step may be repeated. A final collection of labeled cells is accomplished by
15 gravity drainage of the recirculation loop 92. All valves are then closed. The elution recovers at least about 90% of the bound cells. A second elution may be performed to collect the residual bound cells, using the parameters as described above, but including the passage of wash solution
20 through the recirculation loop to more vigorously wash the column. Such a two-step process allows the majority of target cells to escape the more vigorous elution process.

The product collection container 83 now holds the labeled cells and can be removed from the separation device.
25 The separation process also results in the collection of unlabeled cells and other uncontaminated sample components in an unlabeled sample container 85. If a mistake is made in the separation process, the sample may be recovered in the unlabeled sample container and the procedure may be
30 restarted. In addition, the recovery of cells or other components in the unlabeled sample container allows the use of the recovered materials in further separation procedures or other processes. Optionally the cells are directly eluted into a bag suitable for freezing or other storage.
35 In a cell separation process, for example, 10-20% of the target cell population may pass to the unlabeled cell container, but the uncontaminated contents of that container may be reprocessed through the separation device.

Preferably, less than 20% of the target cell population will pass to the unlabeled sample container during a separation process.

The enrichment factor is the number of unlabeled cells that pass through the process per unlabeled cells that are non-specifically retained by the device. Usually the separation/recollection process described above will give an enrichment factor for large scale preparative processes of at least about 1000, more usually at least about 3,000, and preferably at least about 5,000. Large scale processes will usually result in the collection of at least about 107 target cells, more usually at least about 108 target cells. A sample of peripheral blood having a starting population of 0.1% CD34 positive cells will result in the collection of a target cell population of approximately 70-90% purity, corresponding to an enrichment factor of 3000 to 10,000. Similar results may be obtained where the starting sample material is prepared from buffy coat (generally containing about 0.1% progenitor cells) or a leukapheresis product from patients treated with an agent to mobilize CD34+ cells (generally containing about 2.0% progenitor cells).

Example 3

Hematopoietic Progenitor Cell Collection

Sample Preparation

In an exemplary cell separation process, human blood cells provide the sample cell population. Mixed cell populations such as peripheral blood, bone marrow, blood from the umbilical cord or placenta, or fetal blood may be used, and are harvested by standard techniques. Standard techniques are also used in the initial preparation of the cell sample (e.g. Ficoll-Hypaque density separation, centrifugation and supernatant removal, etc.). Typical sample preparation procedures will reduce the volume of the sample, thereby concentrating the target cells and reducing the amount of fluid that must be used in the separation system. By preconcentrating the sample, less antibody is needed for the separation process and binding occurs more

rapidly. The preferred starting material is a leukapheresis product from patients treated with an agent to mobilize CD34+ cells.

5 Magnetic Conjugate Incubation

The magnetic label is an iron/polysaccharide particle conjugated to a murine monoclonal antibody that specifically binds CD34, a surface antigen found on hematopoietic stem and progenitor cells. In a sterile bag, the cell suspension
10 is spun down at 500 x g for 10 minutes. Using a vented spike adapter, the plasma supernatant is withdrawn from the bag, being careful not to remove any white cells. From a starting volume of 600 ml, approximately 95 g of sample is left in the bag. The cell pellet is resuspended in the
15 remaining fluid. Using a sterile syringe and needle, the conjugated monoclonal antibody (10 ml of magnetic reagent containing 200 µg of antibody) is injected into the bag through a coupler. Sterile air (120 cc) is injected into the bag to aid in proper mixing. The bag is sealed and
20 rocked at room temperature for 30 minutes. Normal saline + 0.5% HSA (500 ml) is added to the sample bag, and mixed thoroughly. The sample is centrifuged at 500 x g for 10 minutes. Supernatant (500 grams) is removed from the bag through the coupler. The cell pellet is resuspended in the
25 remaining fluid. The wash steps are repeated. The resulting concentrated cell population is then resuspended and is ready for cell separation.

Cell Separation

30 The stem cell separation procedure takes approximately thirty minutes using an automated system as depicted in Figure 3. The operator first loads the separation device (tubing and column set) onto the instrument and connects the bag containing the wash liquid or buffer and the bag
35 containing the antibody-treated cells (approximately five minutes) to the device. The automated system then washes and primes the fluid circuitry (approximately five minutes) and initiates the separation process (approximately twenty

minutes) as described above. The rest of the run is performed automatically without operator intervention. The instrument will signal that the run is done.

Magnetically labeled cells (e.g. CD34-positive cells) are retained within the separation column by means of magnetic force. The column is then washed and the eluate collected in a discard container. Upon removal of the magnet, the column is again washed and the selected antibody/cell complex is collected in a separate container. The purified CD34-positive cells (or other specific cell population) are then ready for use. A hand sealer may be used to close off the tubing between the stem cell collection container and the rest of the separation device by creating seal points above and below a connecting Luer lock. The stem cell collection container may then be removed.

The collected cells may be cryopreserved or used immediately. The cells may also be subjected to further processing such as ex vivo expansion to enhance the number of stem/progenitor cells to be transplanted. In the absence of an additional removal procedure, the cell suspension will contain a very small quantity of the antibody reagent which remains attached to the cells (>99% of the antibody reagent is unbound and this is removed by a cell wash prior to cell separation).

All publications and patent applications cited in this specification are herein incorporated by reference as if each individual publication or patent application were specifically and individually indicated to be incorporated by reference.

Although the foregoing invention has been described in some detail by way of illustration and example for purposes of clarity of understanding, it will be readily apparent to those of ordinary skill in the art in light of the teachings of this invention that certain changes and modifications may be made thereto without departing from the spirit or scope of the appended claims.

WHAT IS CLAIMED IS:

1. A separation system comprising:
 - (a) a sample container;
 - 5 (b) a prefiltration column connected by a first fluid pathway to said sample container;
 - (c) a separation column connected by a second fluid pathway to said prefiltration column, wherein said separation column comprises a ferromagnetic matrix;
 - 10 (d) a distribution channel connected by a third fluid pathway to said separation chamber, wherein said distribution channel is connected to
 - (e) a product collection container by a fourth fluid pathway,
 - 15 (f) a wash waste container by a fifth fluid pathway, and
 - (g) an unlabeled sample container by a sixth fluid pathway.
- 20 2. The separation system in accordance with Claim 1, wherein said separation column comprises:
 - (a) a nonmagnetic housing having an inlet port, an outlet port and defining a separation chamber; and
 - (b) a fluid permeable matrix of ferromagnetic spheres
 - 25 disposed within said chamber, wherein said spheres are stacked in a lattice configuration thereby forming channels within said matrix.
3. The separation system in accordance with Claim 2,
- 30 wherein said prefiltration column is identical to said separation column.
4. The separation system in accordance with Claim 1, further comprising: a recirculation loop connecting said
- 35 second fluid pathway and said third fluid pathway such that sample which has passed through said separation column may be redirected to said separation column.

5. The separation system in accordance with Claim 4, further comprising: a pump means connected to said recirculation loop to recycle fluid through said recirculation loop and said separation column.
- 5
6. The separation system in accordance with Claim 5, wherein said pump is a peristaltic pump which controls the passage of fluid through the recirculation loop in either direction and at variable speeds.
- 10
7. The separation system in accordance with Claim 1, further comprising:
- (a) a wash of buffer container; and
 - (b) an initial wash waste container,
- 15 wherein said containers are connected by fluid pathways seven and eight, respectively, to said first fluid pathway.
8. The separation system in accordance with Claim 7, wherein said wash or buffer container is also connected via a wash or buffer line to said distribution channel.
- 20
9. The separation system in accordance with Claim 8, wherein said wash or buffer line is further connected to said second fluid pathway by means of a ninth fluid pathway.
- 25
10. The separation system in accordance with Claim 1, further comprising: a filter in the fluid pathway between said sample container and said prefiltration column, wherein said filter removes unwanted components from the sample prior to passage of the sample to said prefiltration column.
- 30
11. The separation system in accordance with Claim 10, wherein said filter has a pore size selected to remove particulates larger than 40 μm .
- 35

12. The separation system in accordance with Claim 1, wherein fluid flow through said fluid pathways of the separation system is controlled by valve means placed within one or more of said fluid pathway(s).

5

13. The separation system in accordance with Claim 12, wherein said fluid pathways are made of a flexible tubing and said valve means are pinch valves which close said fluid pathways by depressing the walls of said tubing against one another.

10

14. The separation system in accordance with Claim 1, further comprising a magnetic field generating means.

15 15. The separation system in accordance with Claim 14, wherein said magnetic field generating means is a permanent magnet or an electromagnet.

16. A separation system, comprising:

20

(a) a separation device comprising:

(i) a separation column that connects by a first fluid pathway to a sample container wherein said separation column comprises non-magnetic housing having a diameter to length ratio of at least 0.2 to 1;

25

(ii) a distribution channel connected by a second fluid pathway to said separation chamber, wherein said distribution channel leads to

(iii) a product collection container,

(iv) a wash waste container, and

30

(v) an unlabeled sample container; and

(b) a separation instrument, comprising a housing including:

(i) a sample container holder;

35 (ii) one or more valve means to control fluid flow through one or more of said fluid pathways;

(iii) a separation column holder; and

(iv) a magnetic field generating means;

wherein said separation device may be installed upon said separation instrument for the performance of a separation process and upon completion of the separation process the separation device may be removed.

5

17. The separation system in accordance with Claim 16, wherein said separation device further comprises a recirculation loop connecting said first fluid pathway and said second fluid pathway such that sample which has passed
10 through said separation column may be redirected to said separation column.

18. The separation system in accordance with Claim 17, wherein said separation instrument is an automated
15 separation instrument, further comprising an automated pump means connected to said recirculation loop.

19. The separation system in accordance with Claim 18, further comprising a motor means to move said separation
20 column holder, and thereby move the separation column, into or out of the magnetic field.

20. The separation system in accordance with Claim 18, further comprising a motor means to move said magnetic field
25 generating means relative to said separation column, and thereby remove the magnetic field from said separation column.

21. The separation system in accordance with Claim 19,
30 further comprising an ultrasonic sensor to detect the presence of fluid in said first fluid pathway.

22. The separation system in accordance with Claim 19, further comprising:
35 (a) a microprocessor means to control said valves, said pump means and said motor, and thereby direct said instrument to perform the appropriate separation operations in a desired sequence; and

(b) a video display to allow an operator to monitor automatic system operation.

23. The separation system in accordance with Claim 22,
5 further comprising an operator keypad to allow the operator to further operate the instrument in a manual mode.

24. A separation system comprising:

(a) a prefiltration column that connects by a first
10 fluid pathway to a sample container;

(b) a separation column connected by a second fluid pathway to said prefiltration column, wherein said separation column comprises

(i) a nonmagnetic housing having an inlet port,
15 an outlet port and defining a separation chamber; and

(ii) a fluid permeable matrix of ferromagnetic spheres disposed within said chamber wherein said spheres are stacked in lattice configuration thereby forming substantially uniform channels between said spheres, and
20 wherein said channels are about 20 to about 200 microns in diameter;

(c) a distribution channel connected by a third fluid pathway to said separation chamber, wherein said distribution channel is connected to

(i) a product collection container by a fourth
25 fluid pathway, and

(ii) a final wash waste container by a fifth fluid pathway,

(iii) an unlabeled sample container by a sixth
30 fluid pathway;

(d) a recirculation loop connecting said second fluid pathway and said third fluid pathway such that a fluid that has passed through said separation column may be recirculated through said separation column; and

(e) a pump connected to said recirculation loop to
35 recycle fluid through said recirculation loop and said separation column.

25. A method for separating a sample into labeled and unlabeled sample components, comprising the steps of:

(a) labeling a component of the sample with a magnetically responsive material;

5 (b) transferring the sample from a sample container through a fluid pathway to a separation column, wherein said separation column comprises a ferromagnetic matrix which in the presence of a magnetic field provides a magnetic field gradient whereby the labeled sample component is retained
10 within said separation column while unlabeled sample component passes through said separation column;

(c) transferring the unlabeled component from said separation column to an unlabeled component container by means of a distribution channel that interconnects said
15 separation column and said container;

(d) removing the magnetic field, thereby releasing the labeled component from said separation column;

(e) redirecting the released labeled component, via a recirculation loop, into said separation column in the
20 presence of a magnetic field thereby performing a second separation of labeled component from the sample, wherein said recirculated labeled component is redirected to said separation column without passage through said sample container;

25 (f) transferring further unlabeled sample component from said separation column to said unlabeled component container via said distribution channel;

(g) removing the magnetic field, thereby again releasing the labeled component from said separation column;
30 and

(h) transferring the labeled component from said separation column to a second collection container via said distribution channel.

35 26. The method according to Claim 25, wherein the labeled component of the sample is labeled with a magnetically responsive material prior to placing the sample into said sample container.

27. The method according to Claim 25, wherein the labeled component of the sample is labeled with a magnetically responsive material within said sample container.
- 5 28. The method according to Claim 25, wherein the sample is transferred from said sample container through a prefiltration column prior to transfer to said separation column.
- 10 29. The method according to Claim 25, wherein a wash fluid is passed through said separation column to facilitate the transfer of the unlabeled component from said separation column to said unlabeled sample container.
- 15 30. The method according to Claim 29, wherein a wash fluid is passed through said separation column to facilitate the recirculation of the labeled component into said separation chamber, and wherein a wash fluid is passed through said separation column to facilitate transfer of the labeled
20 component from said separation chamber to a product collection chamber.
31. The method according to Claim 25, wherein said magnetic field gradient is provided by placing said separation column
25 with the magnetic field of a permanent magnet.
32. A method for separating a sample into labeled and unlabeled sample components, comprising the steps of:
- (a) labeling a component of the sample, in a sample
30 container, with a magnetically responsive material;
- (b) transferring the sample from said sample container through a prefiltration column;
- (c) transferring the sample from said prefiltration
35 column to a separation column, wherein said separation column comprises a ferromagnetic matrix which in the presence of a magnetic field provides a magnetic field gradient whereby the labeled component is retained within

said separation column while unlabeled sample component passes through said separation column;

(d) transferring the unlabeled component which passes from said separation column to an unlabeled component container, via a distribution channel;

(e) removing the magnetic field, thereby releasing the labeled component from said separation column;

(f) redirecting the labeled component, via a recirculation loop, into said separation column in the presence of a magnetic field thereby performing a second separation of labeled component from the sample;

(g) transferring additional unlabeled component, via said distribution channel, from said separation column to said unlabeled sample component container;

(h) removing the magnetic field, thereby again releasing the labeled component from said separation column, and

(i) transferring the labeled component from said separation column to a second container via said distribution channel.

33. A magnetic separator for separating magnetic or magnetically labeled target substances from a sample, the separator comprising:

(a) a nonmagnetic housing having an inlet port, an outlet port and defining a separation chamber having a diameter to length ratio of least 0.2 to 1; and

(b) a fluid permeable matrix of ferromagnetic spheres disposed within said chamber wherein said spheres have an average diameter of about 0.2 to about 0.5 millimeters and are stacked in lattice configuration thereby forming substantially uniform channels of about 20 to about 60 μm in diameter between said spheres,

wherein said matrix is coated with a substantially fluid impermeable coating and is deformation resistant.

34. The magnetic separator in accordance with Claim 33, wherein said non-magnetic housing is plastic, and

wherein said fluid impermeable coating is adherent to said housing.

35. The magnetic separator in accordance with Claim 5 34, further comprising a non-magnetic porous base layer and a non-magnetic porous cap layer between which said spheres are disposed.

36. The magnetic separator in accordance with Claim 10 35, wherein the volume above said porous cap layer, enclosed by said housing, is in a ratio of about 0.1 ml volume to 10 mm of chamber width.

37. The magnetic separator in accordance with Claim 15 36, wherein said spheres have an average diameter of about 0.2 to 0.3 millimeters, and varying not more than about 15% from the average diameter.

38. The magnetic separator in accordance with Claim 20 37, wherein said fluid permeable matrix occupies about 60 to 80% of the total volume of said separation chamber.

39. The magnetic separator in accordance with Claim 25 38, wherein said fluid permeable matrix occupies about 75 to 80% of the total volume of said separation chamber.

40. The magnetic separator in accordance with Claim 30 39, said matrix further comprising a hydrophilic coating and readily wettable surface.

41. The magnetic separator according to Claim 40, wherein said hydrophilic coating is selected from the group consisting of polyvidone, polyvinylpyrrolidine, polyethylene glycol, hydroxyethyl starch and acrylamide.

42. A magnetic separator device for use in separating 35 , magnetic or magnetically labeled target substances from a sample, the device comprising:

(a) a separation column comprising:

(i) a nonmagnetic housing having an inlet port, an outlet port and defining a separation chamber having a diameter to length ratio of least 0.2 to 1; and

5 (ii) a fluid permeable matrix of ferromagnetic spheres disposed within said chamber wherein said spheres have an average diameter of about 0.2 to about 0.5 millimeters and are stacked in lattice configuration thereby forming substantially uniform channels of about 20 to about 60 μm in
10 diameter between said spheres, wherein said matrix is coated with a substantially fluid impermeable coating providing rigidity to resist substantial deformation on placement of said matrix in a magnetic field; and

(b) a filtration device that is connected to said
15 separation column;

wherein said sample first passes through said filtration device in the absence of a magnetic field, and subsequently passes through said separation column in the presence of a magnetic field.

20

43. The magnetic separator device in accordance with Claim 42, wherein said filtration device is a column substantially identical to said separation column. .

25 44. The magnetic separator device in accordance with Claim 42, further comprising a fluid pathway interconnecting said inlet port and said outlet port of said separation column, whereby fluid is recirculated through said separation column.

30

45. The magnetic separator device in accordance with Claim 42, further comprising a suspension filter connected by a fluid pathway to said inlet port of said prefiltration column.

35

46. The magnetic separator device in accordance with Claim 42, wherein said non-magnetic housing of said

separation column is plastic, and wherein said fluid impermeable coating is adherent to said housing.

47. The magnetic separator device in accordance with
5 Claim 46, wherein said separation column further comprises a non-magnetic porous base layer and a non-magnetic porous cap layer between which said spheres are disposed.

48. The magnetic separator in accordance with Claim
10 47, wherein the volume above said porous cap layer, enclosed by said housing, is in a ratio of about 0.1 ml volume to 10 mm of chamber width.

49. A magnetic separation instrument comprising the
15 magnetic separator device of Claim 42 and a magnetic means for the application of said magnetic field to said separation column.

50. The magnetic separation instrument in accordance
20 with Claim 49, wherein said magnetic means is a permanent magnet, and said separation column is retained on a retractable arm by which said separation column is moved into or out of the magnetic field of said permanent magnet.

25 51. The magnetic separator instrument in accordance with Claim 50, further comprising a pump means by which fluid can be recirculated through said fluid pathway at variable speeds and in varying directions.

30 52. The magnetic separator instrument in accordance with Claim 51, further comprising valves for selectively enabling the fluid to flow through said fluid pathway; and a computer for controlling said valves.

35 53. The magnetic separator instrument in accordance with Claim 52, further comprising a bubble detector responsive to the presence of fluid in said fluid pathway.

FIGURE 1





Figure 2







Figure 4



A. CLASSIFICATION OF SUBJECT MATTER

IPC(6) :BO1D 35/06; GO1N 33/553

US CL :Please See Extra Sheet.

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

U.S. : 210/85, 143, 195.1, 201, 222, 257.1, 258, 335, 416.1, 428, 506, 695, 772; 436/526

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A,P	US, A, 5,439,586 (RICHARDS ET AL) 08 AUGUST 1995	1-53
A	US, A, 4,855,045 (REED) 08 AUGUST 1989	1-53
A	US, A, 4,157,323 (YEN ET AL) 05 JUNE 1979	1-53
A	US, A, 4,594,160 (HEITMANN ET AL) 10 JUNE 1986	1-53

☐ Further documents are listed in the continuation of Box C.
 ☐ See patent family annex.

* Special categories of cited documents:	*T	later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
A document defining the general state of the art which is not considered to be of particular relevance	*X*	document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
E earlier document published on or after the international filing date	*Y*	document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
L document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)	*G*	document member of the same patent family
O document referring to an oral disclosure, use, exhibition or other means		
P document published prior to the international filing date but later than the priority date claimed		

Date of the actual completion of the international search

06 MAY 1996

Date of mailing of the international search report

23 MAY 1996

 Name and mailing address of the ISA/US
 Commissioner of Patents and Trademarks
 Box PCT
 Washington, D.C. 20231

Facsimile No. (703) 305-3230

Authorized officer

MATTHEW O. SAVAGE

Telephone No. (703) 308-3854

A. CLASSIFICATION OF SUBJECT MATTER:**US CL :**

210/85, 143, 195.1, 201, 222, 257.1, 258, 335, 416.1, 428, 506, 695, 772; 436/526